

IRON GARD

MAINTENANCE SOLUTIONS

EVERYTHING YOU NEED
TO GET THE JOB DONE.

CLEANERS • GRAPHITE PRODUCTS • RADIATOR PRODUCTS
FUEL CONDITIONERS • HYDRAULIC PRODUCTS • ADHESIVES
GASKETING • THREADLOCKERS • SEALANTS • FLOORING PRODUCTS



CNH ORIGINAL
PARTS

INTRODUCTION

When you choose Iron Gard Maintenance Solutions from CNH Original Parts, you can rest assured that you're choosing the very best. The same no compromises approach we take with our equipment is evident in the quality and performance of the products you'll find in this catalog. Whether you're looking for cleaners, sealants or adhesives, you can trust Iron Gard products from CNH Original Parts to deliver the maintenance solutions you need. If you have any questions or if you'd like to place an order, please don't hesitate to call your CNH Original Parts dealer today.



CLEANERS

Gasket Remover	4
Silicone Polish	4
Glass Cleaner	4
Foaming Engine Degreaser	4
Carb & Choke Cleaner	4
Brake Parts Cleaner	5
All-Purpose Cleaner & Degreaser	5
Surface Cleaner	5
Deluxe Spindle Cleaner	5

ELECTRICAL PRODUCTS

Battery Cleaner	6
Electrical Contact & Parts Cleaner	6
Battery Saver	6
Dielectric Tune-Up Grease	6

GRAPHITE PRODUCTS

Graphite Seed Flow	7
Dispensing Cap	7
Talc/Graphite Seed Flow	7
Graphite Lubricant Non-Stick	7

LUBRICANTS

EP Gear Grease	8
Industrial-Strength Rust Penetrant	8
Heavy-Duty Silicone Lubricant	8
G-n Assembly Paste	8
Anti-Seize Lubricant	8
Dry Film Lube	8
G-4700 Extreme Synthetic Grease	9
Penetrating Oil	9
White Lithium Grease	9
Corn Head Grease	9
Gear Oil	10
Friction Modifier	10
Wheel Bearing Grease	10
Chain & Cable Lube	10

STARTING FLUIDS

Premium Starting Fluid	10
------------------------------	----

FUEL TREATMENT

Diesel Fuel Conditioner	11
Diesel Fuel Anti-Gel	11
Algae Enemy	11

RADIATOR PRODUCTS

Radiator Stop Leak	12
--------------------------	----

HYDRAULIC PRODUCTS

Hydraulic Brake Oil	12
Hydraulic Brake Oil-LHM Fluid	12

ADDITIONAL PRODUCTS

Heavy-Duty Brake Fluid	13
R134A Refrigerant Oil	13
Belt Dressing	13
Power Shift Transmission Fluid	13
Anti-Chatter Additive	13
Synthetic Power Steering Fluid	14
Power Steering Fluid	14
Tilcoat	14

ADHESIVES

Devcon® Magic Bond Epoxy Putty	15
Epoxy Mixer Cups	15
Weatherstrip/Contact Adhesive	15
Devcon® Plastic Welder™	16
Devcon® 5 Minute® Epoxy Amber	16
Permatex® ZipGrip® GPE 3	16
Devcon® Zip-Patch™	16

GASKETING

The Right Stuff® Gasket Maker	17
Permatex® Form-A-Gasket #2 Sealant	17
Permatex® Aviation Form-A-Gasket #3 Sealant	17
Anaerobic Flange Sealant	18
High-Temperature Anaerobic Gasket Maker	18
Anaerobic Gasket Maker	18

GASKETING – RTV

Red RTV Silicone	19
Black RTV Silicone Adhesive Sealant	19
Clear RTV Silicone Adhesive Sealant	19
Ultra Black® Gasket Maker	20
Permatex® Ultra Grey® Gasket Maker	20
Ultra Blue® Gasket Maker	20

THREADLOCKERS

Medium Strength Threadlocker Blue	21
Surface Insensitive Threadlocker Blue	22
High Strength Threadlocker Red	22
Large Diameter Threadlocker Red	22
Permanent Strength Threadlocker Red	22
Permatex® Penetrating Grade Threadlocker Green	23
Permatex® High Strength Threadlocker Red Gel	23
Permatex® Medium Strength Threadlocker Blue Gel	23

THREAD SEALANTS

High-Temperature Thread Sealant	24
---------------------------------------	----

BEARING MOUNTS

Retaining Compound For Close Fits	25
Retaining Compound For Relaxed Fits	25

FLOORING PRODUCTS

Devcon® Epoxy Concrete Sealer	26
Devcon® Concrete Crack Repair	26
Devcon® Floor Patch	26
Devcon® Floor Grip	27
Devcon® Floor Patch FC [Fast Cure]	27

PAINT CHARTS

Agriculture Enamel Paint Chart	28
Construction Enamel Paint Chart	29
All Makes Agriculture & Construction Paint Chart	29
All Makes, Thinner & Primer	29

INDEX

INDEX	30
-------------	----

Clean & Protect

Clean and protect your equipment with Iron Gard's line of degreasers and cleaners. Once your equipment is free of dirt and grease, protect it with Silicone Polish for a long-lasting, brilliant shine.



Gasket Remover

Removes form-in-place chemical gaskets, baked-on cut gaskets, gasket cements, dried oil, grease and paint from any type of metal in minutes. Strips carbon deposits from valves, heads and pistons. Reduces excessive scraping and potential damage to flange surfaces. Safe for use on all types of metals. Not for use on plastic, tile, linoleum or synthetic fabrics.

Item # B505510
Container Size 12 oz / 340 g



Silicone Polish

Apply to clean surfaces with a soft cloth or sponge and allow to dry to a haze, then wipe and buff with a clean cloth. Polishes your farm equipment, construction equipment, cars or trucks to a brilliant hard shine.

Item # FP319
Container Size 16 oz / 473 ml



Glass Cleaner

CNH Original Parts Glass Cleaner will clean, shine and polish all glass and plastic surfaces. Leaves a clear streak-free finish.

Item # ZRG018GLC
Container Size 18.5 oz / 524 g



Foaming Engine Degreaser

Cuts oil, grease, sludge and dirt. Spray on, wait 10 minutes and rinse off. Removes caked-on grease. Water rinsable.

Suggested Applications:

Engine parts, concrete floors, farm and construction equipment

Item # B505512
Container Size 15 oz / 425 g



Carb & Choke Cleaner

CNH Original Parts Carb and Choke Cleaner removes deposited gum, grease and gasoline residue from carburetors, choke linkages and external metal engine parts. Smooths rough idle. Purges excess deposits from fuel intake system to restore power, economy and performance. Also ideal for spray cleaning of varnished steel or cast iron parts normally hand cleaned on bench operations. Helps ensure faster starts, smoother idle and maximum power from your engine. Also cleans and degreases metal parts of all kinds.

Suggested Applications:

Carburetors, choke mechanisms and PCV valves

Item # ZRG017CRBC
Container Size 16 oz / 454 g





Brake Parts Cleaner

CNH Original Parts Brake Parts Cleaner is a non-chlorinated formula specially designed to completely clean all metal brake parts of grease, oil and brake fluid residue. Loosens brake dust for easy removal.

Suggested Applications:
Brakes, tools and equipment

Item #	Container Size
ZRG017BRC	16 oz / 454 g



Surface Cleaner

Fast evaporating cleaner quickly removes oil and grease from metal parts and surfaces. Will not cause corrosion.

Suggested Applications:
Use as a final wash before assembly. Improves gasket, sealant and paint adhesion. Cleans hand tools. Cleans power transmission chains. Cleans oily engine parts. Dissolves motor oil residue. Cleans paint from spray guns.

Item #	Container Size
B505511	11.5 oz / 326 g



B505518

B505517

All-Purpose Cleaner & Degreaser

Biodegradable, all purpose, industrial strength, concentrated cleaner and degreaser. This product is formulated for wipe down, pressure spraying and immersion cleaning process at room temperature or heated. Citrus scented and non-flammable 24-oz spray bottle is a 1:1 dilution, ready to use spray. One gallon is full strength ready for dilution.

Suggested Applications:
Removes grease, grime, oil, cutting fluids, mildew and animal fat. Cleans engine parts, exhaust hoods and drilling rigs. Cleans greasy tools. Cleans cement floors. Water dilutable for glass cleaner. Removes finger prints and smudges.

Item #	Container Size
B505517	22 oz / 651 ml
B505518	1 gal / 3.784 L



Deluxe Spindle Cleaner

A water-based spindle cleaner specifically formulated to keep spindles clean, slick and trouble-free. Helps preserve fiber quality. Cleans up moisture system and prevents scum in tank. Mixes with hard or soft water. Promotes better picker performance. Non-staining.

Item #	Container Size
368847A1	1 gal / 3.784 L

Clean & Protect

Iron Gard battery cleaner dissolves and removes corrosion from battery connectors, cables, fasteners and hold-downs, while neutralizing battery acid. Cleaner changes color, when the cleaning is complete. Once the battery is clean, protect the battery from corrosion, with Iron Gard Battery Saver. Application seals out acid fumes, moisture and dirt, while helping to prevent acid shorts.

Clean electrical parts and contacts, with Iron Gard Contact cleaner. Can be used as a final wash before assembly.



Battery Cleaner

CNH Original Parts Battery Cleaner is an amazingly easy way to remove corrosion from all battery parts. Use to neutralize acid and dissolve corrosion from terminals, cable, hold-downs and boxes. Recommended for all tractors, harvesters, forage and industrial and construction equipment batteries. The color change indicates when the cleaning is complete. No guesswork involved.

Item # **Container Size**
B505514 12 oz / 340 g



Electrical Contact & Parts Cleaner

Fast-evaporating, heavy-duty cleaner removes oil, grease and other contaminants from electrical parts and mechanical equipment. Can be used on hard surfaces including metal associated with electrical and electronic parts. Use as a final wash before assembly – improves gasket, sealant and paint adhesion.

Suggested Applications:
Switches, relays, motor controls, connectors and sensors

Item # **Container Size**
B505513 11.5 oz / 326 g



Battery Saver

CNH Original Parts Battery Saver provides a protective coating that prevents the formation of damaging corrosion. Keeps dirt and other contaminants from interfering with the flow of power. Prolongs battery, cable and clamp life. Recommended for use with CNH Original Parts Battery Cleaner.

Item # **Container Size**
B505515 12 oz / 340 g



Dielectric Tune-Up Grease

Provides a moisture-proof barrier that lubricates and protects equipment from corrosion, salt and dirt. High dielectric strength. Good thermal oxidation and chemical stability.

Suggested Applications:
Ignition systems, spark plug connections, disconnect junctions, electrical assemblies and terminals, cable connectors, battery terminals and lighting connections

Item # **Container Size**
ZPX81150 .33 oz / 9.4 g

Graphite Products

Graphite products from Iron Gard provide lubrication for numerous different applications. The Graphite Seed Flow products provide an environmentally friendly lubricant, that can be applied directly to a planters' seed hopper, to aid in consistent seed flow and constant plant spacing. Iron Gard Graphite Lubricants are greaseless, therefore will not attract dirt and debris. This makes this product ideal for gravity boxes or grain bin applications, to name just a few.



73340734 ▶

◀ 73340370



▲ 73340733

▲ 407486R1

Graphite Seed Flow

Graphite Seed Flow helps seed flow smoothly in planter hoppers and lubricates planter mechanisms. Developed for Cyclo® planters, but this graphite lubricant can be used in other planters as well. Convenient shaker can provide a light covering over bottom of hopper and its working parts. Directions: Fill hopper halfway and shake to add another light covering. Continue filling the hopper with seed and give final light graphite covering over the top. One can contains enough lubricant to treat 42 bushels of seed corn. Dispensing cap sold separately.

Item

407486R1
73340733

Container Size

1 lb Shaker Bottle / 454 g
8 lb Bottle with Optional
Dispensing Cap

Talc/Graphite Seed Flow

(See images above)

50/50 blend of Talc and Graphite. Talc/Graphite Seed Flow helps seed flow smoothly in planter hoppers and lubricates planter mechanisms. Reduces seed bridging and also reduces the planter plate wear. Dispensing cap sold separately.

Item

73340370
73340734

Container Size

1 lb Shaker Bottle / 454 g
8 lb Bottle with Optional Dispensing Cap



▲ 407408R1

▲ 547596R1

▲ 1131916R1



Dispensing Cap

Dispensing cap is designed to fit the 8 lb Graphite and Graphite/Talc Seedflow containers. This unique cap takes the mess out Graphite dispensing and delivers an exact amount of product each time. A simple half turn of the cap handle dispenses the product efficiently – without waste, or worry about spillage – in the field. Cap is re-usable.

Item

73340918

Container Size

Dispensing Cap

Graphite Lubricant Non-Stick

(See images above)

Non-Stick Graphite lubricants can be sprayed brushed or rolled onto any metal or wood surface to reduce sliding friction. Can be used as a lubricant on chains, sprockets, hitches, over-head door tracks, winches and hinges. Use Non-Stick Graphite for seed drum seal wearing ring and market alternator of Cyclo® planters.

Also, as a surface conditioner on gravity boxes, hoppers, chutes, moldboards, planters and markers, forage boxes and wagon beds. Non-Stick Graphite lubricants are the most effective products to prevent hang-up of high moisture grain in hoppers and gravity boxes. Protects metal against rust and corrosion.

Item

1131916R1
547596R1
407408R1

Container Size

1 gal / 3.78 L
1 qt / 946 ml
12 oz / 340 g

Anti-Seize & Lubricants

Check out the wide variety of lubricants and anti-seize compounds available.



EP Gear Grease

CNH Original Parts EP Gear Grease is recommended for use in all gearboxes on implements and is identified in the operator's manuals. Lubricant is an extreme pressure semi-fluid, lithium 12 hydroxystearate, soap-based grease and contains an unleaded EP/anti-wear additive and rust corrosion inhibitors. Semi-fluid grease consists of oils containing a small amount of soap thickener, that impart the general appearance of a very soft grease while retaining the fluid characteristics of a very heavy or viscous oil. Although its semi-fluid consistency minimizes leakage through worn or damaged seals, it has superior adhesion to gears and bearings without adhering to gear case walls. Its consistency ensures immediate rewetting of critical wear points. Safe to use with bronze or brass bushings and gears. Can be used in industrial applications where conventional gear oils cannot, because of worn or missing seals.

Item #	Container Size
9821006	32 oz / 946 ml



Industrial-Strength Rust Penetrant

Penetrates to loosen rusted nuts and bolts quickly. Protects against rust and corrosion. Penetrates and lubricates.

Suggested Applications:
Construction equipment, farm equipment and industrial machinery

Item #	Container Size
B505501	12 oz / 340 g



Heavy-Duty Silicone Lubricant

Superior lubricant that weather-proofs and protects. Works on metals, rubber and canvas. Reduces friction.

Suggested Applications:
Lawn mowers, snow shovels, wood drawers, sliding doors and windows

Item #	Container Size
B505503	12 oz / 340 g



G-n Assembly Paste

(See image above)

G-n Metal Assembly Paste is a multi-purpose, heavy-duty lubricating paste containing a blend of molybdenum disulfide and white solid lubricants in a mineral oil base. It will lubricate beyond the yield point of most metals, reducing wear and help prevent seizing, galling and excessive friction.

Item #	Container Size
384646R1	2.8 oz / 80 g



Anti-Seize Lubricant

A high-performance lubricant that keeps parts free from seizure due to high heat or corrosive atmospheres. Reduces galling of press fitted parts.

Suggested Applications:
Exhaust fasteners, turbo charge fasteners and wheel nuts

Item #	Container Size
ZPX76716	16 oz / 454 g
B505504	12 oz / 340 g



Dry Film Lube

Dry, low-friction lubricant. Does not attract dust or dirt. Can be used to lubricate chains, pins and metal slides. Helps prevent rust and corrosion. Penetrates to help free rusted fasteners.

Item #	Container Size
9673903DS	12 oz / 340 g



G-4700 Extreme Synthetic Grease

Formulated to provide higher load carrying capacity, greater wear resistance and longer service life compared with conventional petroleum-based lubricants. NLGI 2 grease. Provides good compatibility with most industrial and engineering substrates including many plastic and rubber materials. Designed to handle extreme loads and applications involving vibration and/or shock loading. Excellent low temperature torque and water washout resistance.

Suggested Applications:

Rolling element and plain bearings, pivot pins, cams, guides, ways, drive screws, gears, splines and other machine elements. Can be used in most non-food related grease applications such as metal working machines, motors, fans, blowers, conveyors, wheel bearings and custom machinery where heavy-duty, long-lasting lubrication is desired.

Item #	Container Size
86983138	14.1 oz / 400 g

Penetrating Oil

Loosens rusted parts. Prevents corrosion on tools and other parts. Dries out wet engine parts. Stops binding and squeaks.

Item #	Container Size
B505502	12 oz / 340 g



White Lithium Grease

CNH Original Parts White Grease is an aerosolized lithium complex grease, which has exceptional resistance to water and evaporation. Provides good lubrication and reduces friction. Sprays into hard-to-reach places without wash-offs. Helps stop rust and corrosion. Not affected by normal hot and cold temperature extremes.

Suggested Applications:

Slides, hinges and latches, chains, rollers bearings, gears and winches.

Item #	Container Size
ZRG012WGC	12 oz / 340 g

Corn Head Grease

Recommended for use in the gear box of corn head attachments. Extra soft-grade of lubricating grease. Helps fight rust and corrosion. Resists washout from rain and moisture. NLGI Grade No. 0. Cartridge can be used in any standard grease gun.

Item #	Container Size
B95920	14 oz / 397 g



Anti-Seize & Lubricants (Continued)



Gear Oil

High-quality gear oil for gearboxes requiring ISO 220 or AGMA grade 5-gear oil. Gear oil has a tackifier to help the gear oil stick to gears. Suitable for gear boxes containing brass or bronze components.

Item # 865-20567DS
Container Size 32 oz / 946 ml



Wheel Bearing Grease

Composed of EP Grease. Acid, salt and alkali resistant. Water resistant to keep parts lubricated. Formulated to withstand high temperatures.

Item # B505497
Container Size 1 lb / 454 g



Friction Modifier

CNH Original Parts Friction Modifier reduces noise from rear axles and supplements sulfur-phosphorus gear oil additives. See Operator's Manual for specific instructions. Reduces friction in gear boxes. Reduces heat build up.

Item # 9706315DS
Container Size 16 oz / 473 ml



Chain & Cable Lube

For use on construction and agricultural equipment. Helps protect against rust and corrosion. Fast penetrating action. Reduces chain wear. Resists high temperature breakdown. Heavy viscosity reduces throw-off. Increases life of chain and cables.

Item # B505500
Container Size 12 oz / 340 g

Starting Fluids

Iron Gard Premium Starting Fluid is 70% ether, more than triple the industry standard of 20% ether. Use this product for faster cold-weather engine starts, saving time, battery and cylinder wear.

Premium Starting Fluid

(See images to right)

Full 70% ether content for quicker engine starts. For use with gasoline and diesel engines. Extends starter and battery life with quicker starts. Contains upper cylinder lubricant and corrosion inhibitor. For use on trucks, tractors and construction equipment. Not for use with pre-heat manifolds or glow plugs.

Item # ZAD3
Container Size 7.4 oz / 210 g

Item # ZAD4
Container Size 11 oz / 312 g



ZAD3 ▶

◀ ZAD4





Fuel Treatment

Iron Gard Fuel Conditioners are designed to treat or prevent a variety of diesel fuel issues, from cold weather gelling, to algae growth, or just improved overall diesel fuel quality and lubricity.



ZRG032LSC ▲

▲ ZRG016LSC

Diesel Fuel Conditioner

CNH Original Parts Diesel Fuel Conditioner is especially formulated for use with the low-sulfur diesel fuels. This additive will increase the lubricity of diesel fuels and prolong injector pump life. One 16-oz can treats 60 gallons. One 32-oz can treats 120 gallons. Sulfur content of less than 5 ppm makes it safe for ultra-low sulfur diesel fuels.

Item #	Container Size
ZRG016LSC	16 oz / 473 ml
ZRG032LSC	32 oz / 946 ml



Diesel Fuel Anti-Gel

CNH Original Parts diesel fuel anti-gel is a special blend of additives designed to reduce fuel problems related to cold temperatures. Will also help maintain fuel system and injector cleanliness, and prevent fuel oxidation or system corrosion.

Item #	Container Size
ZRG015GELC	15 oz / 444 ml



B50547 ▲

▲ B50546

Algae Enemy

(See images above)

Helps control bacterial growth in diesel fuel. Combats sludge and plugging of filters and injectors. One 16-oz container treats 50 gallons of fuel. One 32-oz container treats 100 gallons of fuel. For use in up to B25 bio-diesel.

Item #	Container Size
B50546	16 oz / 473 ml
B50547	32 oz / 946 ml

Repair & Prevention

Repair or prevent costly cooling system failures with Iron Gard Radiator Stop Leak.

Radiator Stop Leak

(See image to right)

Helps seal small leaks quickly. Helps prevent new leaks. Stays safely in suspension until a leak occurs.

Item #	Container Size
B505508	12 oz / 355 ml



Hydraulic Products

Iron Gard Hydraulic Oils are engineer approved for high performance and continued mechanical reliability.



Hydraulic Brake Oil

For use in CNH Original Parts tractor hydraulic clutch and brake systems. This hydraulic oil is **NOT COMPATIBLE** with brake system rubber component parts designed to be used with DOT type brake fluids. See operator's manual for specific instructions.

Item #	Container Size
73340450	32 oz / 946 ml



Hydraulic Brake Oil-LHM Fluid

Material Spec MAT3630, LHM fluid, meets ISO spec 7308. This hydraulic oil is **NOT COMPATIBLE** with brake system rubber component parts designed to be used with DOT type brake fluids.

Item #	Container Size
86541699DS	32 oz / 946 ml



Preserve & Protect

Iron Gard offers a wide assortment of products to preserve your equipment for longer life and less downtime.



Heavy-Duty Brake Fluid

DOT 3 450°F Brake Fluid for drum and disc brakes. Meets or exceeds SAE and federal specifications.

Item # B505499 **Container Size** 12 oz / 355 ml



R134A Refrigerant Oil

Polyalkalene glycol fluid. R134A compressor lubricant. See operator's manual for specific instructions.

Item # SP20DS **Container Size** 16 oz / 473 ml



Belt Dressing

CNH Original Parts Belt Dressing is designed to soften and lubricate belts. Reduces slippage and improves transfer of power. Prevents premature failure caused by belt slippage.

Item # ZRG011BELC **Container Size** 11 oz / 312 g



Power Shift Transmission Fluid

Add to transmission reservoir as needed. See operator's manual for specific instructions. For some twin disk transmissions.

Item # 99000396 **Container Size** 1 gal / 3.785 L



Anti-Chatter Additive

See operator's manual for specific instructions. Stops wet brake chatter.

Item # 251403 **Container Size** 64 oz / 1.92 L

Preserve & Protect (Continued)



Synthetic Power Steering Fluid

Add to power steering reservoir as needed. Suitable for all climates, including cold, northern climates. See operator's manual for specific instructions. Used for transmission, hydraulic, and differential fluids.

Meets the following specs:

- John Deere – J20C, J20D
- AGCO – improved power fluid 821XL
- Ford New Holland
 - ESN-M2C134-D
 - FNHA-2-C-201, FNHA-2-C-200
- Massey Ferguson
 - M1135, M1141, M1127, M1129A
- White Farm Equipment – Q-1826
- Case Corporation
 - JIC-143, JIC-145,
 - MS 1206, MS 1207, MS 1209, MS 1210 (TCH)
- Oliver – Type 55
- Minneapolis – Moline Fluids
- Caterpillar – TO-2
- Renk – Bus ATF 873, 874 A/B
- Kubota – Super UDT, UDT
- International Harvester – B6
- Deutz – Allis 821XL

Item #	Container Size
THDSS	32 fl oz / 946 ml



▲ 1132221N

◀ 1131548R2

▲ 991049R2

Tilcoat

(See images above)

Specialized oil-based coating designed to protect valuable field equipment during non-use periods. Product is formulated to release from tillage tools upon their insertion and use in the ground. Lead-free formula that dries to a non-toxic film and provides short term protection. Fast scouring, resists rust and easy application.

Suggested Applications:

Tillage equipment, mould boards, plow shares, disks, sweeps and shovels

Item #	Container Size
1132221N	12 oz / 340 g
991049R2	1 qt / 946 ml
1131548R2	1 gal / 3.78 L



Power Steering Fluid

Add to power steering reservoir as needed. Not for use in temperatures below zero degrees Fahrenheit (0°F). See operator's manual for specific instructions

Item #	Container Size
73340638	32 fl oz / 946 ml





Epoxy Adhesives

Advanced epoxy adhesives from Iron Gard are used for structural bonding, potting and encapsulating, and come in a variety of cure times and package sizes.



Devcon® Magic Bond Epoxy Putty

Seals leaks and repairs gouges in steel, aluminum, wood, fiberglass concrete and ceramics. Two color stick ensures thorough mixing. Cures in 30 minutes. Can be painted, sanded, machines tapped or drilled.

Item # ZPX11600
Container Size 4 oz / 114 g



Weatherstrip/Contact Adhesive

(See image above)

Fast-drying, neoprene-based adhesive for bonding rubber, insulation, weather stripping and other porous materials. Sets to a tack-free surface in 3 to 4 minutes. Allows repositioning of parts after initial contact. Withstands extremes of freezing or high-heat conditions. Fuel, solvent and anti-freeze resistant.

Suggested Applications:

Replacing and maintaining weather-stripping on windows and doors on trucks, cars and off-road equipment

Item # ZPX31390
Container Size 5 fl oz / 147 ml



Epoxy Mixer Cups

A pre-measured, fast-curing, two-part epoxy in its own easy-to-use mixing cup. Will bond and patch a wide variety of materials. For use on wood, concrete, metal, plastics, glass and ceramic. Ideal for parts with large gaps. Parts repaired in 5 minutes, with full cure in 24 hours.

Suggested Applications:

Bond name plates, shift handles to levers, insulation. Repair broken trim, knobs and other parts.

Item # ZPX21425
Container Size 10 x .14 oz (4g) Cups

Epoxy Adhesives (Continued)



Devcon® Plastic Welder™

Toughened straw-colored adhesive for bonds to engineered plastics such as ABS, PVC, metals and composites.

Item #
ZPX14300

Container Size
25 ml



Devcon® 5 Minute® Epoxy Amber

Rapid curing, general purpose, amber-colored adhesive/encapsulant that bonds metals, wood and ceramic.

Item #
ZPX14250

Container Size
25 ml

Devcon® Zip-Patch™

(See image above)

Seals leaks and gouges in fiberglass, PVC piping. Can turn pressure back on in 1 hour.

Suggested Applications

Repair leaks in PVC piping and gouge leaks in plastic fertilizer tank

Item #
ZPX11500

Container Size

One 4" x 9" Adhesive Impregnated Patch Kit



Permatex® ZipGrip® GPE 3

General purpose Cyanoacrylate for bonding metals, plastic and rubber in all combinations.

Item #
ZPX70145

Container Size
Three 2 g





Gasket Makers

Iron Gard gasket makers offer significant performance advantages which include superior oil resistance, superior torque retention, along with high-temperature resistance.



The Right Stuff® Gasket Maker

Makes high-performance black elastomeric rubber gaskets in one minute. Non-corrosive, with superior flexibility and adhesion. Equipment can be returned to service immediately. Blowout resistant and outperforms precut gaskets. Temperature resistant to 500°F.

Suggested Applications:

Construction equipment, farm equipment and industrial machinery

Item #
ZPX25223

Container Size
4 oz / 113.4 g



Permatex® Form-A-Gasket #2 Sealant

Reliable, paste-like gasket sealant/dressing/coating. Sets slowly to a pliable film best suited for non-rigid, vibrating assemblies. Resists fuels and other solvents. For use in applications to 400°F.

Suggested Applications:

Coating cut gaskets to hold in place and improve sealing

Item #
ZPX80500

Container Size
80 ml



Permatex® Aviation Form-A-Gasket #3 Sealant

A brushable, non-hardening gasket dressing and sealant that holds gaskets in place. Dries slowly to a pliable form. Sealer for use with close fitting parts. Resistant to gasoline and other solvents. Suitable for continuous temperatures of 400°F.

Suggested Applications:

Gasket coating or sealing close fitting parts, water pump gaskets, oil pan gaskets, timing gear covers and coolant hose connections.

Item #
ZPX18130

Container Size
16 oz / 473 ml

Gasket Makers (Continued)



ZPX51530

ZPX51550

Anaerobic Flange Sealant

Flexible, gasketing material for use on rigid assemblies and machined flanges with less than 0.15" gap. OEM approved. Eliminates pre-cut, preformed, paper and rubber cut gaskets. Flexes with flanges that move in service.

Suggested Applications:

As specified in CNH Original Parts service manuals to seal flanged assemblies

Item #	Container Size
ZPX51530	10.1 fl oz / 300 ml
ZPX51550	1.69 fl oz / 50 ml



High-Temperature Anaerobic Gasket Maker

(See image above)

A high-temperature sealant specifically engineered for making or dressing gaskets in rigid assemblies. Able to withstand temperatures to 400°F (204°C), fills gaps to 0.010" (0.254mm) and permits clamping loads to be maintained for strong leak-proof assemblies.

Suggested Applications:

Sealing rigid, flat machined metal surfaces

Item #	Container Size
ZPX51050	1.69 fl oz / 50 ml



Anaerobic Gasket Maker

(See image above)

Ideal for on-the-spot and emergency repairs, or when a conventional gasket is not available. Seals to 300°F (149°C), fills gaps to 0.050" (1.27mm). Can be used on a variety of metal surfaces including aluminum. Forms a flexible, solvent-resistant seal that will not tear or decay. Parts disassemble easily even after extended service and old gasket material can be removed in minutes with a putty knife.

Suggested Applications:

Sealing flexible metal assemblies

Item #	Container Size
ZPX51850	1.69 fl oz / 50 ml

CNH Iron Gard Branded Thread Sealants/Gasketing

Product	Item Number	Container Size	Color	Viscosity cP	Seal to Operating Pressure	Temperature Range	Specific Gravity
High-Temperature Anaerobic Gasket Maker	ZPX51050	50 ml tube	Red	288,000	1-12 hrs	-65°F to 400°F	1.08
Anaerobic Flange Sealant	ZPX51550 ZPX51530	50 ml tube 300 ml cart	Purple	275,000	1-12 hrs	-65°F to 300°F	1.10
Anaerobic Gasket Maker	ZPX51850	50 ml tube	Red	750,000	4-24 hrs	-65°F to 300°F	1.13
High-Temperature Thread Sealant	ZPX59250	50 ml tube	White	350,000	24 hrs	-65°F to 400°F	1.21

RTV

Iron Gard RTV silicone products offer a wide temperature rating while providing excellent sealing and bonding properties, along with oil resistance.



▲ ZPX30564

▲ ZPX81160

Red RTV Silicone

A high-temperature RTV silicone suited to form in place gasket applications subjected to temperatures up to 605°F intermittent. Sensor-safe.

Suggested Applications:

Use where RTV silicone is specified in high-temperature or heavy-duty applications.

Item #	Container Size
ZPX30564	7.25 oz Power Can / 205 g
ZPX81160	3 oz / 85 g

Black RTV Silicone Adhesive Sealant

An all-purpose RTV silicone adhesive/sealant suited for a wide variety of indoor and outdoor sealing, bonding and weatherproofing uses. Cures into a flexible sealant that will not harden or crack over time.

Suggested Applications:

Engine covers, front wheel assist covers, sheet metal covers, caulk joints and seal. Electrical boxes, seal electrical terminals and bond insulations.

Item #	Container Size
ZPX81158	3 oz / 85 g

▶ ZPX80855



▲ ZPX80050

◀ ZPX30562

Clear RTV Silicone Adhesive Sealant

(See images above)

An all-purpose RTV adhesive and sealant for a variety of bonding and sealing jobs. Clear formulation makes it particularly well suited for jobs that require a neat, cosmetic appearance.

Suggested Applications:

Windshield frames, lights and cable panels

Item #	Container Size
ZPX80050	3 oz / 85 g
ZPX30562	7.25 oz Power Can / 205 g
ZPX80855	10.1 fl oz / 300 ml



RTV (Continued)



Ultra Black® Gasket Maker

Fast curing, sensor-safe, low-odor and non-corrosive, Ultra Black meets performance specs of OE silicone gaskets. Retains high-flexibility and oil-resistance properties through use of a patented adhesion system. Temperature range -65°F to 650°F intermittent.

Suggested Applications:

Pump housings, machine tools, compressors, gearboxes, valve covers, oil pans and transmission pans

Item #	Container Size
ZPX82180	3.35 oz / 95 g



Permatex® Ultra Grey® Gasket Maker

Designed for high-torque applications requiring a unique RTV gasket. Fills gaps of up to 0.25" when fully cured. Exceeds manufacturer's performance requirements. Low odor, non-corrosive. Outstanding oil and coolant resistance. Temperature range of -65°F to 650°F intermittent; resists shop and auto fluids and vibration.

Suggested Applications:

Pump housings, machine tools, compressors, gearboxes, valve covers, oil pans and transmission pans

Item #	Container Size
ZPX18572	80 ml



ZPX85519 ▶

◀ ZPX81724

Ultra Blue® Gasket Maker

(See images above)

A high-performance RTV silicone well suited for a wide variety of gasketing uses. It is 3 times more oil resistant than standard RTV's. Outstanding oil resistance and flexibility. Eight times more flex than cork or composite gaskets. Sensor-safe and non-corrosive.

Suggested Applications:

Use where a non-corrosive RTV is required and where maximum hot oil resistance is desired.

Item #	Container Size
ZPX81724	3.35 oz / 95 g
ZPX85519	9.5 oz Power Can / 269 g



Liquid Threadlockers... Providing Threaded Fastener Reliability

Iron Gard Liquid Threadlockers are superior to conventional lock washers, nylon inserts, and other mechanical devices because they secure the entire fastener assembly against loosening from shock or vibration and maintain fastener clamping forces. Threadlockers also seal the threads against leakage and prevent rust and corrosion. Available in a variety of strengths and temperature ranges, threadlockers remain the most reliable way to lock and seal threaded fasteners of all shapes and sizes, either before or after assembly.



ZPX24236

ZPX24210


Medium Strength Threadlocker Blue

This blue, general-purpose threadlocker, locks and seals threaded parts. Use on nuts, bolts and screws. Ensures that parts do not loosen prematurely due to shock and vibration. Medium strength allows easy removal.

Suggested Applications:

Lock and seal hydraulic pump screws, parking brake bolts, transmission case cover bolts. Lock seat bracket bolts, retain axle seals and planet pins end covers.

Item #	Container Size
ZPX24210	.34 fl oz / 10 ml
ZPX24236	1.22 fl oz / 36 ml



VS.



CNH Original Parts Liquid Threadlocker

Entire threaded area filled with threadlocker. ONE DROP FITS ALL! Threads sealed – moisture can't get inside.

Lock Washer

Contact only under bolt – bolt can vibrate loose. Must use right size. Threads open – moisture can get in causing corrosion.

CNH Iron Gard Branded/Permatex® Liquid Threadlockers

Product	Item Number	Container Size	Typical Use	Color	Viscosity cP	Break/Prevail Torque in-lbs ¹	Temperature Range	Fixture Time ² / Full Cure	Fixture with Primer	Specific Gravity
CNH® Iron Gard Medium Strength Threadlocker BLUE	ZPX24210 ZPX24236	10 ml bottle 36 ml bottle	1/4" to 3/4" (6-20mm)	Blue	1,200/6,000 Thixotropic	115/53	-65°F to 300°F (-54° to 149°C)	20 min/ 24 hrs	5 min	1.00
CNH® Iron Gard Surface Insensitive Threadlocker BLUE	ZPX24310	10 ml bottle	1/4" to 3/4" (6-20mm)	Blue	2,250/12,000 Thixotropic	180/62	-65°F to 300°F (-54° to 149°C)	20 min/ 24 hrs	5 min	1.08
CNH® Iron Gard Permanent Strength Threadlocker RED	ZPX26210 ZPX26236	10 ml bottle 36 ml bottle	3/8" to 1" (10-25mm)	Red	1,800/5,000 Thixotropic	189/275	-65°F to 300°F (-54° to 149°C)	20 min/ 24 hrs	5 min	1.10
CNH® Iron Gard High Strength Threadlocker RED	ZPX27110 ZPX27136	10 ml bottle 36 ml bottle	3/8" to 1" (10-25mm)	Red	500	230/225	-65°F to 300°F (-54° to 149°C)	20 min/ 24 hrs	5 min	1.10
CNH® Iron Gard Large Diameter Threadlocker RED	ZPX27736	36 ml bottle	1" & greater (25mm+)	Red	7,000	250/200	-65°F to 300°F (-54° to 149°C)	60 min/ 24 hrs	5 min	1.12
Permatex® Penetrating Grade Threadlocker GREEN	ZPX29050	50 ml bottle	#2 to 1/2" (2.2-12mm)	Green	12	90/310	-65°F to 300°F (-54° to 149°C)	20 min/ 24 hrs	5 min	1.08

¹ .375" x 16 phosphate steel

² Fixture strength is equivalent to 20% of full cure strength

Liquid Threadlockers (Continued)



Surface Insensitive Threadlocker Blue

A removable strength, general-purpose threadlocking adhesive especially well suited for fasteners between 1/4" and 3/4" diameter (6 to 20mm). Applied to threaded components before assembly, surface insensitive has controlled lubricity for accurate clamp loads. Parts can be separated using hand tools.

Suggested Applications:

Machine tools, presses, pumps, compressors, mounting bolts, gear boxes and where specified in service manuals

Item #	Container Size
ZPX24310	.34 fl oz / 10 ml



ZPX26236

ZPX26210

Permanent Strength Threadlocker Red

A high-strength adhesive to lock and seal large threads where lubricity for controlled torque tension is required. Apply to fasteners between 3/8" and 1" in size before assembly. Disassemble while hot (450°F).

Suggested Applications:

Lock and seal high-strength bolts as specified in service manuals. All fasteners that must withstand heavy shock, vibration or extreme chemical or environmental conditions.

Item #	Container Size
ZPX26210	.34 fl oz / 10 ml
ZPX26236	1.22 fl oz / 36 ml



ZPX27136

ZPX27110

High Strength Threadlocker Red

A high-strength adhesive to lock and seal threads when maximum locking strength is required. Designed for large fasteners (3/8" to 1") and permanent assemblies. Heat parts to 450°F to disassemble.

Suggested Applications:

Lock and seal PTO return spring bolt, lock and seal tractor roller cap screws, lock wheel studs.

Item #	Container Size
ZPX27110	.34 fl oz / 10 ml
ZPX27136	1.22 fl oz / 36 ml



Large Diameter Threadlocker Red

A high-strength adhesive for locking and sealing large bolts and studs 1" or larger in diameter. Heat may be required to weaken bond before parts can be disassembled. Disassemble while hot (450°F).

Suggested Applications:

Frame brackets, suspension fasteners, shock absorber mounts and wheel studs

Item #	Container Size
ZPX27736	1.22 fl oz / 36 ml

Liquid Threadlockers (Continued)

Permatex® GEL TWIST™ Threadlockers

Product	Item Number	Container Size	Typical Use	Color	Viscosity cP	Break / Prevail Torque in-lbs ¹	Temperature Range	Fixture Time ² Full Cure	Specific Gravity
Permatex® Medium Strength Threadlocker BLUE Gel	ZPX24010	10 g Gel TWIST™ Applicator	1/4" to 1" (6-25mm)	Blue	75,000/900,000 Thixotropic	115/53	-65° to 300°F (-54° to 149°C)	15 min/24 hrs	1.15
Permatex® High Strength Threadlocker RED Gel	ZPX27010	10 g Gel TWIST™ Applicator	3/8" to 1" (10-25mm) & greater	Red	75,000/900,000 Thixotropic	175/230	-65° to 300°F (-54° to 149°C)	15 min/24 hrs	1.13



Permatex® Penetrating Grade Threadlocker Green

A low-viscosity, thread-locking liquid, that wicks along the threads of pre-assembled fasteners to secure them in place. For use on small, reassembled fasteners (up to 1/2"). Localized heat and hand tools are required for disassembly.

Suggested Applications:

Set screws, adjustment screws, pre-assembled fasteners, electrical connectors and carburetor adjustment screws

Item # **Container Size**
 ZPX29050 1.69 fl oz / 50 ml



Permatex® Medium Strength Threadlocker Blue Gel

All purpose strength threadlocker gel that reliably secures all nut and bolt applications 1/4" to 1".

Item # **Container Size**
 ZPX24010 10 g



Permatex® High Strength Threadlocker Red Gel

A high-strength threadlocker red gel for heavy-duty applications. Ideal for reliably securing all nut and bolt applications 3/8" to 1"

Item # **Container Size**
 ZPX27010 10 g



¹ .375" x 16 phosphate steel

² Fixture strength is equivalent to 20% of full cure strength

Thread Sealants

Iron Gard Thread Sealants seal and secure metal pipes and fittings. By filling the space between threaded metal parts. Thread sealants prevent leakage caused by vibration loosening, tape shredding, solvent evaporation, damaged threads and temperature cycling. Designed for low-and-pressure applications, Thread sealants seal instantly for online low-pressure testing. When fully cured, they seal to burst strength of most piping systems. The high lubricating properties of Iron Gard Thread Sealants ease assembly and prevent galling of the threads. For system repairs, parts may be disassembled with basic hand tools.



High-Temperature Thread Sealant

A high-performance sealant that seals threaded metal fittings instantly. Lubricates for easy assembly and cures to lock against vibration loosening. Outperforms Teflon tape, will not shred.

Suggested Applications:

Tapered pipe threads, pipe plugs, fuel line fittings, hydraulic fittings, air line fittings, and brake and power steering fittings

Item #	Container Size
ZPX59250	1.69 fl oz / 50 ml



Bearing Mounts

Iron Gard Retaining Compounds are designed to bond non-threaded, cylindrical, metal assemblies by filling the voids between close-fitting metal parts. Retaining compounds harden to create a solid, one-piece assembly and can be used to lock keyways, secure splines, augment press fits and strengthen interference fits. Use them to prevent wear on new components, or restore the fit to worn or out-of-tolerance parts. Retaining compounds seal joints against leakage and prevent fretting and corrosion. Formulated in a variety of viscosities, strength characteristics, gap-filling abilities, and temperature ranges, Iron Gard Retaining Compounds can solve even the most difficult retaining applications.



Retaining Compound For Close Fits

A high-strength sealant that retains and seals cylindrical assemblies. Increases the holding strength of press fits and retains slip fits. For use on bearings, bushings, sleeves, keyways and splines.

Suggested Applications:

Clutch hub to piston carrier, engine block heaters, engine plug hubs, oil seals, bushings, bearings, ring gear bolts and differential lock pins.

Item # **Container Size**
 ZPX60936 1.22 fl oz / 36 ml



Retaining Compound For Relaxed Fits

A high-strength, room-temperature curing adhesive used to join fitted cylindrical parts. It fixtures in 10 minutes and provides shear strength of 4000 psi in 24 hours. Capable of filling diametrical gap clearances up to 0.010" (0.27mm).

Suggested Applications:

Gears, wheels, pulleys, cams, collars, flywheels, sprockets and rotors to shafts

Item # **Container Size**
 ZPX68036 1.22 fl oz / 36 ml



CNH Iron Gard Branded Retaining Compounds

Product	Item Number	Container Size	Color	Maximum Diametral Gap Fill	Viscosity cP	Shear Strength psi	Temperature Range	Fixture Time/ Full Cure (on Steel)	Specific Gravity
Bearing Mount For Close Fits	ZPX60936	36 ml bottle	Green	.005"	125	1-12 hrs	-65°F to 300°F (-54° to 149°C)	10 min/ 24 hrs	1.10
Bearing Mount For Relaxed Fits	ZPX68036	36 ml bottle	Green	.015"	350,000	1,250	-65°F to 300°F (-54° to 149°C)	10 min/ 24 hrs	1.10

Floor Repair/Patching Compounds

100% solid epoxy-based polymer for patching, rebuilding, and resurfacing concrete, brick, stucco and block.



Devcon® Epoxy Concrete Sealer

Self leveling non VOC clear epoxy sealer to seal concrete floors. Outstanding resistance to chemicals, acids alkalis and hydrocarbons. Bonds to a damp surface.

Suggested Applications:

Garage floors, warehouse floors and milking parlors

Item #	Container Size
ZPX12560	2 gal



ZPX13100 ▲

Devcon® Floor Patch

(See images above)

All-purpose, easy-to-mix epoxy concrete patching compound. Three times the strength of typical concrete. Cures in 16 hours.

Suggested Applications:

Milking parlor floors, garage floors and concrete silos

Item #	Container Size
ZPX13100	10 lb
ZPX13120	40 lb



Devcon® Concrete Crack Repair

Self leveling crack repair urethane that bonds to brick, concrete and stone to help waterproof concrete from water.

Suggested Applications:

All floors with cracks

Item #	Container Size
ZPX13400	11 oz Caulking Cartridge



Floor Repair & Resurfacing Product Selector Guide

Flooring Applications	Floor Patch™ FC	Deep Pour Grout™	Epoxy Concrete Sealer	Floor Grip™	Concrete Crack Repair
Acid-Resistant Coating			▼		
Anchoring Bolts in Concrete	▼	▼			
Anti-Skid Floors/Ramps/Docks				▼	
Chemical Containment Coatings			▼		
Chocking Equipment	▼	▼			
Coatings (Impact, Abrasion)			▼	▼	
Expansion Joints	▼				▼
Floor (Hole-Filling & Patching)	▼	▼			
Leveling Floors		▼			
Meat & Poultry Plants	▼	▼	▼	▼	
Milk Parlors				▼	
Warehouse Floor Coatings			▼		
Wet/Damp Surface Coatings	▼		▼	▼	



Devcon® Floor Grip

(See image above)

Heavy-duty epoxy compound with silicone carbide granules produces a nonskid surface. Excellent adhesion to metal, concrete brick and aluminum and will bond to a wet surface. Can be applied at temperatures as low as 40°F. Bonds to a damp surface.

Suggested Applications:

Ramps, steps in milking parlor, metal stair rungs on silos and tanks, and loading docks

Item #
ZPX13090

Container Size
2 gal



Devcon® Floor Patch FC [Fast Cure]

(See image above)

All purpose easy-to-mix epoxy concrete patching compound. Three times the strength of typical concrete. Cures in 3 hours.

Suggested Applications:

Milking parlor floors, garage floors and concrete silos

Item #
ZPX13110

Container Size
10 lb



PAINT CHARTS



Paint Charts

One stop shop to get your Case, New Holland and Kobelco paints to match your equipment. Order these parts along with all of your Iron Gard maintenance solutions and chemicals available now from your locate CNH Original Parts dealer.

Agriculture Enamel Paint Chart

HIGH PERFORMANCE			COLOR	PART NUMBER PER SIZE			
MFG	MODEL	YEAR	NAME	SPRAY	QUART	GALLON	FIVES
IH	All	1969 – 1981	2150 Red	991012N	991010R2LF	B90882LF	
Case IH / IH	All	1961 – Current	MS 3 Gloss Red	B17566N	B17564	B17562	B504438
IH	All	1969 – 1981	935 White	991115N	991116R2	B90888	
Case IH / IH	All	1988 – 1999	MS 45 Non-Glare Black	990121N	1132129R1	B90886	B93387
Case IH / IH	All	2000 – Current	CNH Original Parts Dark Gray	B96104	B96105	B96106	
Case IH / IH	All	2000 – Current	Wheat	B96107			
Case IH / IH	All	1961 – Current	MS 19 Silver	B17567N	B17565	B17563	
IH	All	1981 – 1988	MS 50 Gloss Black	B17680N	B17681	B17682	B93386
Case	All	Pre – 1973	MS 6 Desert Sunset	B17650N	B17651LF	B17652LF	
Case	All	1974 – 1985	MS 2 Power Red	B17670N	B17671LF	B17672LF	
Case	All	1974 – 1985	MS 7 Power White	B17655N	B17656	B17657	
Steiger	All	All Green Models	Green	1132224N		1131611R1LF	
IH	All		4419 Yellow				

STANDARD			COLOR	PART NUMBER PER SIZE		
MFG	MODEL	YEAR	NAME	SPRAY	QUART	GALLON
Versatile	All	All	Red	99000330DS	99000331DS	99000332DS
Versatile	All	All	Yellow	99000333DS	99000334DS	99000335DS
Ford	Tractors	39 – 62	Gray	M1J957SE5DS	M1J957SE2DS	M1J957SE3DS
Ford	Tractors	65 – 94	Gray	M20J1750SE5DS	M20J1750SE2DS	M20J1750SE3DS
Ford	Tractors	39 – 62	Red	M1J956SE5DSL	M1J956SE2DSL	M1J956SE3DSL
Ford	Tractors	79 – Current	Black (Flat)	M1724GSE5DS	M1724GSE2DS	
Ford		75 – 80	White	M1619ASE5DS	M1619ASE2DS	M1619ASE3DS
Ford		74 – 80	Consumer White	M1525ASE5DS	M1525ASE2DS	
Ford / New Holland	Tractors	63 – 99	Blue	9613385DS	9613386DS	9613387DS
Ford / New Holland	Tractors	94 – 99	Chassis Gray	9624696DS	9624697DS	9673509DS
Ford / New Holland	Tractors	94 – Current	Blanco White	9624698DS	9624699DS	
Ford / New Holland	Tractors	99 – 2000	Gray Ral 7024	86109004DS	86109005DS	86109006DS
New Holland	Hay & Forage	All	Red	70780DS	70365DS	70036DS
New Holland	Hay & Forage	Pre 1984	Yellow	70781DS	70106DSL	70107DSL
New Holland	Hay & Forage	84 – 99	Yellow	94806DS	94807DS	94808DS
New Holland	Hay & Forage	79 – Current	Black (Flat)	M1724GSE5DS	M1724GSE2DS	
New Holland	Hay & Forage	99 – Current	Bright Yellow	86109000DS	86109001DS	86109002DS
New Holland	Hay & Forage	2000 – Current	Dark Gray	B96104DS	B96105DS	B96106DS

Agriculture Enamel Paint Chart (Continued)

STANDARD			COLOR	PART NUMBER PER SIZE		
MFG	MODEL	YEAR	NAME	SPRAY	QUART	GALLON
New Holland	Tractors	2000 – Current	Blue	86109144DS	86109141DS	86109142DS
New Holland	Tractors	2000 – Current	CNH Original Parts Dark Gray	B96104DS	B96105DS	B96106DS
New Holland	Tractors	Boomer 8N	Red	73340255	73340256	
New Holland	Tractors	Boomer 8N	Beige	73340257	73340258	

Construction Enamel Paint Chart

HIGH PERFORMANCE			COLOR	PART NUMBER PER SIZE			
MFG	MODEL	YEAR	NAME	SPRAY	QUART	GALLON	FIVES
Case	All	Pre – 1975	MS 10 Ind/Federal Yellow	991098N	991084R2LF	B90890LF	
Case	All	1975 – 1983	MS 11 Power Yellow	B17665N	B17666LF	B17667LF	
Case	All	1983 – Current	MS 42 Power Tan	B17660N	B17661	B17662	B17663
Case	All	1983 – 1994	MS 44 Brown	B17675N	B17676	B17677	
Case	All	1995 – 2000	MS 37 Gray	B93228N	B93229	B93230	
Case	All	2000 – Current	CE Gray	B96025	B96026	B96027	
Ford / New Holland		67 – 80	Yellow	M5394ASE5DSL	M5394ASE2DSL	M5394ASE3DSL	
Ford / New Holland		81 – 99	Yellow	M5771ASE5DS	M5771ASE2DS	M5771ASE3DS	
Ford / New Holland		99 –	Bright Yellow	86109000DS	86109001DS	86109002DS	
Ford / New Holland	All	All	Black (Medium Gloss)	94792DS	9624700DS		
Ford / New Holland		99 – 2000	Gray Ral 7024	86109004DS	86109005DS	86109006DS	
Ford / New Holland		2000 –	CE Gray	B96025DS	B96026DS	B96027DS	
Ford / New Holland		2006 –	Light Gray	87298699	87298700		
Kobelco	Dynamic Acera M/C, Acera Mark 8	Sep 2006 – Current	Bright Yellow	KSP0201-612Y		KSP0201-601Y	
Kobelco	Mark-III, Mi/C, IV, DA	1991 – Current	Yellow	KSP1000-812Y		KSP1000-801Y	
Kobelco	SR & Compacts	ALL	Yellow, Dark	KSP7000-112Y		KSP7000-101Y	
Kobelco	Mark III	1991	Yellow, Light	KSP1000-712Y			
Kobelco	Lower Mark IV, DA	ALL	Gray	KSP4000-212G		KSP4000-201G	
Kobelco	Counterweight, Compartment Doors (matte) SR & Compact	ALL	Gray, Dark	KSP7000-312GD		KSP7000-301GD	
Kobelco	Lower Body Trim Mark-IV	ALL	Gray, Metallic	KSP4000-212GT			
Kobelco	Cab SR, DA, Compact		Gray, Neutral	KSP7000-212GN		KSP7000-210GN	
Kobelco	Lower SR & Compact	ALL	Gray, Lower	KSP5000-312G		KSP5000-301G	
Kobelco	Early SR, Compacts, Mark-V		Blue Green	KSP7000-112GR		KSP7000-101GR	
Kobelco	Mark-III, Mi/C	1991	Blue	KSP1000-812B		KSP1000-801B	
Kobelco	Cab Mark-IV		Silver	KSP4000-112S		KSP4000-101S	
Kobelco	Acera MK8 – Cab		Gray	87299902			

All Makes Agriculture & Construction Paint Chart

ALL MAKES DESCRIPTION	PART NUMBER PER SIZE		
	SPRAY	QUART	GALLON
AC Orange	B505031	B505032	B505033
Cat Yellow	B505052	N/A	B505053
Deere Ind Yellow	B505054	N/A	B505055
Cub Cadet White	B505051	N/A	N/A
Cub Cadet Yellow	B505050	N/A	N/A
Deere Ag Yellow	B505028	B505029	B505030
Deere Green	B505025	B505026	B505027
Gloss White	B505056	N/A	B505057
MF Red	B505042	B505043	B505044
Kubota Orange	B505034	B505035	N/A
MF Flint Gray	B505045	B505046	B505047
MF Gray	B505048	B505049	N/A

ALL MAKES DESCRIPTION	PART NUMBER PER SIZE		
	SPRAY	QUART	GALLON
Gloss Black	533916DS	443216DS	443116DS
IH Red	533901DS	443201DS	443101DS
IH White	533915DS	443215DS	N/A
Case Red	533904DS	443204DS	443104DS
Aluminum	996356N	990506R1	N/A
Semi Gloss Black	94792DS	9624700DS	N/A
Flat Black	533919DS	N/A	N/A
Hesston Red	B505040	B505041	N/A
New Holland Red	B505036	B505037	N/A
New Holland Yellow	B505038	B505039	N/A
Ford Blue	B505020	B505021	B505022
Ford Gray	B505023	B505024	N/A

All Makes, Thinner & Primer

NAME	PART NUMBER PER SIZE			
	SPRAY	QUART	GALLON	FIVES
Thinner	—	B17692	B17693	B17694
Primer – MS 43 Gray	B91253N	B91254	B91255	—
Primer – MS 43 Red Oxide	1131655N	991078R1	B90892	—
Primer – MS 43 Buff Primer	B95400	B95401	B95402	—

INDEX

Item #	Page	Item #	Page	Item #	Page
1131548R2	14	87298699	28	B17666LF	28
1131655N	29	87298700	28	B17667LF	28
1131916R1	7	87299902	29	B17670N	28
1132129R1	28	865-20567DS	10	B17671LF	28
1132221N	14	94792DS	28, 29	B17675N	28
1132224N	28	94806DS	28	B17676	28
251403	13	94807DS	28	B17677	28
368847A1	5	94808DS	28	B17680N	28
384646R1	8	9613385DS	28	B17681	28
407408R1	7	9613386DS	28	B17692	29
407486R1	7	9613387DS	28	B17693	29
443101DS	29	9624696DS	28	B17694	29
443104DS	29	9624697DS	28	B50546	11
443116DS	29	9624698DS	28	B50547	11
443201DS	29	9624699DS	28	B90890LF	28
443204DS	29	9624700DS	28, 29	B90892	29
443215DS	29	9673509DS	28	B91253N	29
443216DS	29	9673903DS	8	B91254	29
533901DS	29	9706315DS	10	B91255	29
533904DS	29	9821006	8	B93228N	28
533915DS	29	99000330DS	28	B93229	28
533916DS	29	99000331DS	28	B93230	28
533919DS	29	99000332DS	28	B93386	28
547596R1	7	99000333DS	28	B93387	28
70036DS	28	99000334DS	28	B95400	29
70106DSL	28	99000335DS	28	B95401	29
70107DSL	28	99000396	13	B95402	29
70365DS	28	990121N	28	B95920	9
70780DS	28	990506R1	29	B96025	28
70781DS	28	991010R2LF	28	B96025DS	28
73340255	28	991012N	28	B96026	28
73340256	28	991049R2	14	B96026DS	28
73340257	28	991078R1	29	B96027	28
73340258	28	991084R2LF	28	B96027DS	28
73340370	7	991098N	28	B96104	28
73340450	12	991115N	28	B96104DS	28
73340638	14	991116R2	28	B96105	28
73340733	7	996356N	29	B96105DS	28
73340734	7	B17564	28	B96106DS	28
73340918	7	B17565	28	B96107	28
86109000DS	28	B17566N	28	B504438	28
86109001DS	28	B17567N	28	B505020	29
86109002DS	28	B17650N	28	B505021	29
86109004DS	28	B17651LF	28	B505022	29
86109005DS	28	B17655N	28	B505023	29
86109006DS	28	B17656	28	B505024	29
86109141DS	28	B17660N	28	B505025	29
86109142DS	28	B17661	28	B505026	29
86109144DS	28	B17662	28	B505027	29
86541699DS	12	B17663	28	B505028	29
86983138	9	B17665N	28	B505029	29

Item #	Page	Item #	Page	Item #	Page
B505030	29	KSP1000-812Y	28	ZPX14300	16
B505031	29	KSP4000-101S	29	ZPX18130	17
B505032	29	KSP4000-112S	29	ZPX18572	20
B505033	29	KSP4000-201G	29	ZPX21425	15
B505034	29	KSP4000-212G	29	ZPX24010	23
B505035	29	KSP4000-212GT	29	ZPX24210	21
B505036	29	KSP5000-301G	29	ZPX24236	21
B505037	29	KSP5000-312G	29	ZPX24310	22
B505038	29	KSP7000-101GR	29	ZPX25223	17
B505039	29	KSP7000-101Y	28	ZPX27010	23
B505040	29	KSP7000-112GR	29	ZPX27110	22
B505041	29	KSP7000-112Y	28	ZPX27136	22
B505042	29	KSP7000-210GN	29	ZPX27736	22
B505043	29	KSP7000-212GN	29	ZPX29050	23
B505044	29	KSP7000-301GD	29	ZPX30562	19
B505045	29	KSP7000-312GD	29	ZPX30564	19
B505046	29	M1J956SE2DSL	28	ZPX31390	15
B505047	29	M1J956SE3DSL	28	ZPX51050	18
B505048	29	M1J956SE5DSL	28	ZPX51530	18
B505049	29	M1J957SE2DS	28	ZPX51550	18
B505050	29	M1J957SE3DS	28	ZPX51850	18
B505051	29	M1J957SE5DS	28	ZPX59250	24
B505052	29	M20J1750SE2DS	28	ZPX60936	25
B505053	29	M20J1750SE3DS	28	ZPX68036	25
B505054	29	M20J1750SE5DS	28	ZPX70145	16
B505055	29	M1525ASE2DS	28	ZPX76716	8
B505056	29	M1525ASE5DS	28	ZPX80050	19
B505057	29	M1619ASE2DS	28	ZPX80500	17
B505497	10	M1619ASE3DS	28	ZPX80855	19
B505499	13	M1619ASE5DS	28	ZPX81150	6
B505500	10	M1724GSE2DS	28	ZPX81158	19
B505501	8	M1724GSE5DS	28	ZPX81160	19
B505502	9	M5394ASE2DSL	28	ZPX81724	20
B505503	8	M5394ASE3DSL	28	ZPX82180	20
B505504	8	M5394ASE5DSL	28	ZPX85519	20
B505508	12	M5771ASE2DS	28	ZRG011BELC	13
B505510	4	M5771ASE3DS	28	ZRG012WGC	9
B505511	5	M5771ASE5DS	28	ZRG015GELC	11
B505512	4	SP20DS	13	ZRG016LSC	11
B505513	6	THDSS	14	ZRG017BRC	5
B505514	6	ZAD3	10	ZRG017CRBC	4
B505515	6	ZAD4	10	ZRG018GLC	4
B505517	5	ZPX11500	16	ZRG032LSC	11
B505518	5	ZPX11600	15		
FP319	4	ZPX12560	26		
KSP0201-601Y	28	ZPX13090	27		
KSP0201-612Y	28	ZPX13100	26		
KSP1000-712Y	28	ZPX13110	27		
KSP1000-801B	29	ZPX13120	26		
KSP1000-801Y	28	ZPX13400	26		
KSP1000-812B	29	ZPX14250	16		



PM-15260 Issued 12/10 Replaces: PM-8560

© 2010 CNH America LLC. All rights reserved. CNH is a registered trademark of CNH America LLC. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH America LLC, are the property of those respective companies.

SOLD & SERVICED BY: